

THE BEST GLOBAL LEADER

For the past 25 years, KME has been manufacturing, supplying, and installing equipment suitable for merchant ships and offshore projects, as well as commissioning to Korean shipyards. We consider product technology and quality as our top priority, and we are actively cooperating with customers' requirements. Despite our current customer satisfaction levels, we will continue developing new business field and finding new markets. The best quality, best service, new product development under a

management philosophy make our customer higher satisfied.



CONTENTS



COMPANY OVERVIEW







GLOBAL SERVICE NETWORK

KORMARINE EXHIBITION

CERTIFICATION





Ceo Greeting

"KME, with the unwavering passion of **Initial Intention** and racing towards its goals."



We have grown through constant challenges and innovation like a racehorse that never loses sight of its target. We at KME have always strived to create the highest value.

Together with our cherished customers, who we have formed valuable relationships with, KME will continue to build a more advanced future.

We earnestly seek your continued interest and support as we embark on this journey of growth with us.

CEO & President
Jae-Youn Seong





Company Overview

It's a company introduction.

- KME Co.,Ltd
-) JAE-YOUN SEONG
- 1999.03.16
- ♀ 29, NAKDONG-DAERO 1302 BEON-GIL, SASANG-GU, BUSAN, KOREA, 46910
- www.h-kme.com

• BUSSINESS FIELD MARINE & ONSHORE & NEARSHORE & OFFSHORE, SPECIAL DIVISION

• SUPPLY SCOPE ACCOMMODATION & ELECTRIC PARTS ITEMS SUPPLY, ENGINEERING, COMMISSIONING, INSTALLATION

TEL: +82-51-327-2670~2 / TID: +82-51-327-8761 / FAX: 82-51-327-2673 / E-MAIL: <u>sales@h-kme.com</u>





Company Values

Company management principles



Ne maintain consistency and reliability ensuring trust in every endeavor.



Unit Toilet Factory

Unit Toilet Factory





2024. 07	Astro sole agency in Marine Segment
2023. 12	Registered vendor to KANGNAM Shipbuilding
2023. 09	Registered vendor to MODEC
2023. 08	Registered vendor to SEATRIUM
2022. 05	Registered vendor to HSG Sungdong Shipbuilding
2022. 04	Acquired ISO 45001:2018 certification
2022. 04	Registered vendor to DAE SUN Shipbuilding & Engineering Co., Ltd.
2022. 02	Registered vendor to Hyundai Heavy Industries
2021.10	Distributor Agreement with Orga BV
2021.09	Registered vendor to Zvezda Shipbuilding in Russia
2021.03	Awarded the 55th Taxpayer Day National Tax Service President Award
2021.02	Acquired patent application for LED navigation lights with heating film
2020. 06	Registered vendor to Hanjin Heavy Industries
2020. 01	Acquired patent application for grounding material C-clamp for ships
2020.01	Registered Ship name Board to SAMSUNG HEAVY INDUSTRIES CO., LTD.
2019. 10	Registered vendor to Hyundai Mipo Dockyard (HMD) Co., Ltd.
2019. 05	Registered as a design partner of Oriental Marine Tech
2019. 01	Registered as a design partner of DSME



2017. 08	Contracted an Agent with INTERTEC in Germany (Protected operating conditions)
2017. 03	Contracted an Agent with STAHL in Germany (Explosion protection)
2016.10	Open Engineering office in Geoje Okpo
2016.09	Registered Ice Class (-55℃ USE) Navigation & Signal Light at Korean Intellectual Property Office
2016.09	Registered design of B-15 Fire Class Switch & Socket Back Box at Korean Intellectual Property Office
2016. 02	Registered design of LED type Ship name Board Light by law firm CHANG JO
2015. 11	Appointed company for Korea military service
2015.09	Acquired CE Certification for Junction box(Electric Heat Tracing System)
2015. 07	Acquired DNV Type approval certificate for KAISER B15 class fire protection box
2015. 01	Contracted an Agent with DHR in Netherlands (Arctic version lighting fixtures)
2014. 11	Registered design for pipe clamp at Korean Intellectual Property Office
2014. 08	Joined the Korea Venture Business Association
2014.06	Registered vendor to DAEWOO SHIPBUILDING & MARINE ENGINEERING, CO., LTDLow Location Light for H.3401
2014.04	Contracted an Agent with THERMON in USA (Heat Tracing System Manufacturer)
2013. 10	Registered vendor to SAMSUNG HEAVY INDUSTRIES CO., LTD.
2013. 10	Contracted an Agent with MARAHRENS in Germany (Low Location Light Manufacturer)
2013. 10	Acquired company R&D Center Certification by KOITA
2013. 07	Changed the company's location to the current site in Samrak-dong, Busan



2013. 02	Received Certificate of Venture Business
2012. 11	Contracted an Agent with KAISER in Germany (B-15 FIRE CLASS Box Insulation)
2012. 11	Acquired Multi Receptacle Box IP56 Testing Certificate (KOLAS)
2012. 10	Registered design of distribution box for passenger ship's cabin at Korean Intellectual Property Office
2012. 05	Registered utility model of distribution box for shipping's cabin at Korean Intellectual Property Office
2011. 12	Registered utility model of socket protecting cover of distribution box at Korean Intellectual Property Office
2011. 10	Developed and supplied Management Control System for passenger ship's cabin
2010. 10	Developed and supplied Dist. Panel Board for passenger ship's cabin [DSME H7509/10]
2010. 05	Developed and supplied Dist. Panel Board for passenger ship's cabin [SAMSUNG SHI HN1807/08]
2009. 10	Acquired UL & CE certification for Lighting Fixtures (FL. MIRROR LIGHT etc.)
2009. 03	Acquired ISO9001:14001 certification
2009. 02	Established KME Co., Ltd.
2008. 12	Designated overseas certification business company by the SMBA [UL, CE]
2008.01	Supplied shipping bathroom and toilet hardware and cabinet
2006.06	Developed and supplied shipping bathroom and cabinet for unit toilet
2006. 05	Developed and supplied explosion-proof Junction box for special ship [FPSO, DRILL SHIP]
2004. 01	Contracted an Agent with ABTECH.
2003. 08	Received Fire Alarm System DNV type approval



1999.03	Established Korea Electrics
2000.01	Manufactured and supplied shipping Junction Box
2000.02	Contracted a Distributor with LEGRAND in France
2000.05	Developed and supplied Box for passenger ship [DSME MOBY-LINE]
2001.01	Developed and supplied Box for passenger ship [SAMSUNG MINOANG LINE]
2002.01	Manufactured and supplied explosion-proof Junction Box



Customer

KME works with world-class companies.

• REGISTERED SHIPYARD (KOREA)



• REGISTERED SHIPYARD (OVERSEAS)






Organization Structure

We will grow together based on the best expertise and trust.







Company Facilities

It's a company building.





Kormarine Exhibition





www.h-kme.co.kr


We, KME CO.,LTD have a higher self-esteem for our electric engineering and product quality. But, not satisfied with the current customer's satisfaction we will continue developing new business field and finding new markets. The best quality, best service, new product development under a management philosophy make our customer higher satisfied.

Supply Products










WORLD LEADER IN INDUSTRIAL PROCESS HEATING





HEAT TRACING END MARKETS

- · Petroleum Production
- · Refining and Gas Processing
- · LNG Tank Foundations, Terminals & Pipelines · Petroleum Production
- \cdot Power Generation
- · Chemical Production
- · Snow & Ice Melting
- · Pharmaceuticals
- Mining
- · Wastewater Management
- \cdot Arctic Marine







WORLD LEADER IN INDUSTRIAL PROCESS HEATING



BSX™

- Freeze Protection and
- Temperature
- Maintenance to 65°C
- Maximum Exposure
 Temperature 85°C



KSX™

- Freeze Protection and Temperature Maintenance up to 121°c
- Maximum Exposure Temperature 121°c



HTSX™

- Freeze Protection and Temperature Maintenance to 150 °C
- Maximum Exposure
 Temperature 250°C



HPT™

- \cdot Freeze Protection and
- Temperature Maintenance
- up to 215°C
- Maximum Exposure
 Temperature 260°C



MIQ™

- Freeze Protection and Temperature Maintenance to 500°C
- Maximum Exposure
 Temperature 600°C

- WE HAVE HEATING CABLES FOR ALL YOUR TEMPERATURE NEEDS -







ZP (Power Junction box)

Non-metallic kits are designed to fabricate power connections of an electric heat trace circuit.



ZE / ZS (End Termination Kit)

Non metallic kits are designed to fabricate inline splices of an electric heat trace circuit.



ZT (Thermostat Junction Box)

ZT is designed to provide pipe-wall or tankwall sensing control of electric heat trace circuits.



ECM

(Electronic control Junction Box)

Terminator ECM is an electronic control module specifically designed for controlling electric heat trace circuits. Serves as both the temperature control as well as the sensor and power connection for a heat trace circuit.



ZE-B (LED End of Circuit Light Kit)

Non metallic kits are designed to fabricate inline splices of an electric heat trace circuit.





Terminator[™] Heating Cable Connection/Termination Kits

Designed and manufactured for use with Thermon heating cables.



Features and Benefits . . .

Engineered Polymer Construction

Minimum installation temperature -60°C Exposure rating +232°C Corrosion resistant UV resistant High impact resistant

Terminal Block Forward Design

Easy access to terminal block for wiring Snap-on DIN rail for permanent mounting

Design and Installation Flexibility

 One kit can serve as a power, splice, tee and end connection Above thermal insulation Easy access to allow heating circuits to be checked and inspected


Triple-Cavity Grommet

Multiple cable entry capacity Independent sealing for each heating cable · Integral triple cavity grommet provides strain-relief for the cable

Complies to Worldwide Approval Requirements

Suitable for use in potentially explosive atmospheres Certified for use in ordinary (nonclassified) areas, hazardous (classified) areas, and Zone 1 and Zone 2 classified areas Provides IP66 (Type 4X) rating Same termination system can be used anywhere in the world

> ZP... power connection kit Is designed for connecting up to three heating cables to power. The heating cable and incoming power are connected in a terminal block utilizing nickel-plated copper terminals to ensure the electrical integrity of the connection over time.



ZL... End-of-circuit light kit is designed to provide visual indication of an energized heating circuit. The kit may be utilized as and end termination or a power connection. Electrical connections are made in a terminal block utilizing nickel-plated copper terminals to ensure the electrical integrity of the connection over time.





ZE-B... End-of-circuit light Kit is designed to provide visual indication of an energized heating circuit. The Standard Terminator Beacon utilizes a high intensity green LED assembly for superior day or night visibility. This light is also available with high intensity red LED.




























ORGA HELIDECK LIGHTING

1) HELIDECK LIGHTING SYSTEM






- \cdot Compact and rugged construction
- \cdot Resistance to vibration
- · Integrated terminal box
- \cdot Quick opening for installation
- LED perimeter lights with very long operating life (up to 50.00hours)





ORGA HELIDECK LIGHTING

② AIDS TO NAVIGATION SYSTEM



KME Co., Ltd.

PHOENIX MECANO EX ENCLOSURES

APPLICATED TO DSME TCO PROJECT



- \cdot Range comprises sizes of 75 x 80 x 55 mm to 405 x 400 x 120 mm
- Supplied as component-certified empty enclosures and pre-assembled as Ex e or Ex ia approved enclosures
- Body consists of glass-fibre-reinforced polyester with a graphite additive





- \cdot Suitable for use in harsh and aggressive environments
- \cdot Sizes from 100 x 100 x 61 mm to 200 x 600 x 121 mm
- Body takes the form of a steel structure with an raised sealing edge on the base




PHOENIX MECANO EX ENCLOSURES

APPLICATED TO DSME TCO PROJECT



- \cdot A broad range of products is available
- \cdot Sizes from 64 x 58 x 34 mm to 600 x 600 x 200 mm
- Suitable for universal use in aggressive environments and in various climate zones
- \cdot Body consists of die-cast aluminum AlSi 12



ROSE



EX COMBI BOX

- Provides an elegant and rationally priced remedy in the structuring of Ex control enclosures
- \cdot Available in three sizes 177 x 177 x 145 mm,
- \cdot 177 x 360 x 145 mm and 360 x 360 x 145 mm
- \cdot A further highlight is the facility for easy wall-mounting





NAVIGATION LIGHTS WITH LED OR INCANDESCENT BULB FOR SAFETY AT SEA



DHR230RCL

APPLICATION

- All types of seagoing vessels, such as tugs, pilot vessels, high speed vessels et cetera

· CONTROL PANEL FUNCTIONS

- On/off switch of the light source
- On/off switch of the panel
- Two-step speed control
- Focus control
- Pan/tilt through joystick

SPECIFICATIONS







Maintenance friendly

Waterproof IP66

Light Weight

Construction



Robust design



SINCE 1922

NAVIGATION LIGHTS WITH LED OR INCANDESCENT BULB FOR SAFETY AT SEA



DHR320RCP

· APPLICATION

- All types of seagoing vessels, such as tugs, pilot vessels, high speed vessels et cetera

· CONTROL PANEL FUNCTIONS

- On/off switch of the light source
- On/off switch of the panel
- Two-step speed control
- Focus control
- Pan/tilt through joystick

SPECIFICATIONS

LED technology





Light Weight Construction



Maintenance friendly

Focus control

Waterproof IP66





NAVIGATION LIGHTS WITH LED OR INCANDESCENT BULB FOR SAFETY AT SEA



DHR70N POLAR NAVIGATION LIGHT

· APPLICATION

- Sea-going vessels navigating in Arctic regions of more than 50m in length / Inland navigation

· SPECIFICATIONS







NAVIGATION LIGHTS WITH LED OR INCANDESCENT BULB FOR SAFETY AT SEA





DHR80N POLAR DHR80N (-52°C to 55°C) (-40°C to 55°C)

DHR80 LED POLAR NAVIGATION LIGHT

- APPLICATION
 - Sea-going vessels over 50m in length

MATERIALS

- Black, hard anodized seawater resistant aluminium
- POM insulation sleeves to prevent galvanic

corrosion

- UV Resistant borosilicate glass lens
- Epoxy potted power supply for maximum protection

SPECIFICATIONS







Excellent thermal management



Maintenance friendly

230 VDC (-20% / +30%)



Main and spare LED Modules




INTERTEC INSTRUMENTATION ENCLOSURES



ENCLOSURES

Composite-GRP offers amazing protection possibilities

- Ingress protection (to IP68)
- · Fire safety (to 120 minutes)
- · Extreme thermal insulation (Arctic conditions)
- Heat resistance (to 160°C)
- · Explosion proofing (Ex e, Ex p, CSA/NEMA 4X)
- · Proof against wind, blast, earthquake
- \cdot Anti-static
- · Corrosion resistance
- \cdot UV resistance
- \cdot Leak resistance
- \cdot Wireless friendly, or EMC shielded
- Frangibility



INTERTEC exploits GRP's intrinsic efficiency to design highly-optimized solutions

Good thermal efficiency relies on enclosure structural materials, and the positioning of internal Elements.

'Thermal short cuts caused by insulation gaps joints or connections such as this cable gland in a steel cabinet, can dramatically decrease thermal efficiency, leading to cold spots and condensation.

Perfectly uniform insulation - with no thermal short cuts from gaps, joints or fixings - is achieved by INTERTEC's 'embedded' insulation technique – as connections - such as a tube - are made with purpose-designed components to ensure insulation efficiency



INTERTEC INSTRUMENTATION ENCLOSURES



ENCLOSURES : BROAD CHOICE AND ADAPTABILITY



Two-part enclosures are easy to panel mount, with tube entry via top or base. MULTIBOX has thick and shallow sections, either of which can be used as the door. 12 sizes.



Diagonally opening enclosures give clear access to field equipment, and may be installed vertically or horizontally. DIABOX allows tube entry via rear or base. 5 sizes.



MINIBOX is sized to provide cost-effective housing to protect close-coupled single-transmitter installations.



UNIBOX enclosures swing open for easy access to all four faces of field equipment.

They are ideal where tube entry is made via the base. 4 sizes.




INTERTEC INSTRUMENTATION ENCLOSURES



ENCLOSURES (SD 22 / 40 / 50 / 100 / 150)

Transmitter below Shade SD 40

Heating and Cooling System





Sensitive electric equipment or electronic devices are installed in instrument enclosures and protected against the effects of the sun by the various shades



HELLA MARINE CRUISE SHIP LIGHTING



KD-1280DN/W-C (IP23 / IP44)

OUTPUT

CONSUMPTION



· KD-1280DN-C, IP23					
750lm	12.5W	143-155MM	IP 23	85	
LIGHT OUTPUT	POWER CONSUMPTION	CUT OUT	PROTECTION CLASS	CRI	
750lm	12.5W	143-155MM	IP 44	85	
LIGHT	POWER	CUT OUT	PROTECTION	CRI	

CLASS



LED Colours : 2700K , 3000K, 4000K



Power Supply : 230V

Opening Angles : 85°

Luminous Intensity Distance / Lux 3000 K

	85°
0,5 m	1m / 3200
1,0 m	2,1m / 800
1,5 m	3,1m / 350
2,0 m	4,2m / 200
2,5 m	5,2m / 125
3,0 m	6,3m / 85



HELLA MARINE CRUISE SHIP LIGHTING





•	KD-1	16/	4/2	20D	N-W,	IP23
---	-------------	-----	-----	-----	------	------

700lm	11W	108MM	IP 23	90
LIGHT OUTPUT	POWER CONSUMPTION	CUT OUT	PROTECTION CLASS	CRI

· KD-116/4/20/DW-W, IP55

700lm	11W	102MM	IP 55	90
LIGHT OUTPUT	POWER CONSUMPTION	CUT OUT	PROTECTION CLASS	CRI



LED Colours : 2700K , 3000K, 4000K



Power Supply: 230V



Opening Angles: 60°, 40°, 20°

	Luminous Inte	Luminous Intensity Distance /Lux 3000 K		
	60 °	40 °	15 °	
0,5 m	0,6m / 2600	0,3m / 5200		
1,0 m	1,1m / 650	0,7m / 1300		
1,5 m	1,7m / 290	1,0m / 580		
2,0 m	2,3m / 160	1,4m / 325		
2,5 m	2,8m / 105	1,7m / 210		
3,0 m	3,4m / 72	2,1m / 145		



LEGRAND SCOKET & SWITCH



SOCKET





- \cdot Finishes : White
- \cdot Connection method : with screws
- \cdot Characteristics : 10 A 250 VAC
- · Capacity : 2 x 4mm
- \cdot Stripping : 9mm
- Screwdriver : cross-head 2 or 4mm flat-blade





- \cdot Finishes : White
- Connection method : automatic terminals
- \cdot Characteristics : 10 A 250 VAC
- \cdot Capacity : 2 x 1.5mm²
- Stripping : 12mm





Australlan type

- \cdot Finishes : White
- \cdot Connection method : with screws
- \cdot Characteristics : 10 A 250 VAC
- \cdot Capacity : 2 x 4mm²
- Stripping : 13mm
- Screwdriver : Cross-head 2 or 4mm flat-blade





- · Finishes : White
- · Connection method : with screws
- · Characteristics : 10/16 A 250 VAC
- · Capacity : 2 x 4mm
- · Stripping : 10mm
- · Screwdriver : 4mm flat-blade



LEGRAND SCOKET & SWITCH

USB CHARGING SOCKET



Type-A

- · For recharging portable devices
- · Conform to IEC 62684-2011-01
- \cdot Surge protection > 1kV
- \cdot Consumption in passive mode < 0.07 W
- Power supply AC/DC efficiency at highest level (VI)
- \cdot 2 x 2.5mm screw terminals
- · Class II SELV
- · Supplied cordless
- · 5 V 2.4 A 12 W





- \cdot Universal charger for portable devices
- · Conform to IEC 62680-1-3
- \cdot Surge protection > 1kV
- \cdot Consumption in passive mode < 0.07 W
- Power supply AC/DC efficiency at highest level (VI)
- \cdot 2 x 2.5mm screw terminals
- · Class II SELV
- · Supplied cordless
- 5 V 3 A 15 W



LEGRAND SCOKET & SWITCH

COLOUR-LIGHTING DIMMERS

Common

- \cdot Allow the user to create lighting ambiances
- \cdot For (LEDs) DALI ballasts and drivers
- · For controlling max. 21 RGB (Red/Green/Blue)
- \cdot Iuminaires
- \cdot Configuration via ``learn" button
- Ideal for show-rooms, shops, restaurants, hotels, beauty salong
- Work with power supply Cat.No 0 035 15
- White



Dimmer – 1area

· Allows manual change of colours





Dimmer – 1 to 4 area

- \cdot Allows the creation of up to 4 lighting ambiances in up to 4 areas
- · For installation in 2-module flush-mounting box depth 50mm
- Multicolour dimming
- · Light adjustments :
- colours : via touch chromatic circle
- intensity : via bargraph
- · Supplied with support



LEGRAND SCOKET & SWITCH

SWITCH & RJ45



SWITCH

- \cdot Degree of impact strength (IK) : IK04
- Nominal voltage : 250 V
- \cdot Rated current : 10 A
- \cdot Switching current for fluorescent lamps : 10 AX
- · Connection type : Screwed terminal
- Min. depth of built-in installation box : 30 mm
- \cdot Operating / setting temperature : -5-50 °C
- \cdot Storage temperature : -10-70 °C
- \cdot Voltage type : AC
- · Frequency : 50-60 Hz



RJ 45

- \cdot Data rate up to 10 GigaBit/s.
- \cdot Support high capacity PoE applications.
- Power over Ethernet pass electric power along with data on twisted pair Ethernet cabling.

- Equipped with a transparent protective dust cover protecting the connector.
- White



DECKMA NAVIGATION & LIGHTING CONTROL PANEL



CONTROL PANEL NLS3000






APPLICATION

In general, the system is meant for control and monitor the ships navigation lights. In addition, this system is also capable of control the navigation lights heater and also the outdoor deck illumination lights. The system monitors and handles all of its multiple power supplies and is capable of manually and automatically select the power supplies in case of a failure of one of these.

SHIP MIMIC

In addition to the LANTERN button indication, all lantern states are also indicated in a mimic. Main and backup lanterns are merge together here. They are indicated at their schematic position and with their name and real color.





Supply Items

「ACCOMMODATION PARTS」

- \cdot UNIT TOILET
- · LED SHIP'S NAME BOARD
- · LABORATORY FURNITURES & EQUIPMENT
- · MEDICAL OXYGEN SYSTEM
- · MEDICAL EQUIPMENT

- · WORKSHOP EQUIPMENT
- · GYMNASIUM EQUIPMENT
- · ENTERTAINMENT EQUIPMENT
- · SAUNA BOOTH
- · GALLEY, LAUNDRY, CATERING FURNITURE

- · MARAHRENS : SAFETY SIGNS
- · LLL(LOW LOCATION LIGHTING) SYSTEM
- · CONFERENCE ROOM
- · SCREEN GOLF
- · CITADEL



UNIT TOILET

High-quality Customized Toilet System





PREFABRICATED WET UNITS

With many years of experience and specialised competence, KME offer fully fitted wet units. The KME wet units are ideal for marine accommodations, from cruise ships to offshore installations. The KME wet units, whether standard or custom made, are manufactured according to the strictest rules and regulations and are fabricated from only first class materials.

In our design the emphasis is on using durable solutions to ensure maximum quality, comfort and well-being of our customers, whether being a ship owner, ship yard or end user.

The units are manufactured with great deal of consideration given to the ease of handling and installation.

Throughout the production process the units are subjected to strict quality control to ensure that all of our materials conform to our policy of supplying only first class quality.

KME products can be specially manufactured according to customer requirements and pursue the highest product quality.



Thank you




Bath & Shower Type

HIGH-END UNIT

KME UNIT TOILET provides type-specific functions, is durable, designed and systemized, and provides one finished product.

We can directly produce and supply products of Various designs, such as shower booth type, bathtub type as well as the standard of the customer.









HIGH-END TYPE PREFABRICATED WET UNIT

We can directly produce and supply products of various designs, such as shower booth type, bathtub type, as well as the standard of the customer.



SHOWER TYPE

- \cdot Direct production and supply of products.
- \cdot Create as requested by the customer.



BATH TYPE

- \cdot Direct production and supply of products.
- \cdot Create as requested by the customer.



No	Description	Specification	Model no	Q'TY	/ SET
NO	Description	Specification	Model no	Shower	Bath
1	FLOOR	MOSAIC TILE ON 3.2 mm STEEL PLATE (GROUTING : GRAY CEMENT)	KME STANDARD	1	1
2	INSIDE WALL PANEL	PAINTED ON 0.6mm GALV'D STEEL PLATE W/15mm MINERAL WOOL, TOTAL THK. 30mm	KME STANDARD	1	1
3	OUTSIDE WALL PANEL	PVC LAMINATED ON 0.6mm GALV'D STEEL PLATE W/15mm MINERAL WOOL, TOTAL THK. 20mm	KME STANDARD	1	1
4	DOOR FRAME	BAKED ENAMEL PAINTED ON 1.5mm STEEL PLATE CLEAR OPENING (600CW x 1800CH, 800CW x 1800CH (HOSPITAL ONLY))	KME STANDARD	1	1
-	DOOR BLADE W/LOCK	PVC LAMINATED ON 0.6mm GALV'D STEEL PLATE DOOR LOCK : INDICATOR MORTISE LATCH	KME STANDARD	1	1
5	WATER CLOSET (YARD SUPPLY)	WALL MOUNTED VACUUM TYPE WHITE VITREOUS CHINA W/BIDET, "YARD SUPPLY & KME INSTALL"	-	1	1
6	SOIL PIPE (VACUUM SYSTEM)	Ø50 OUTLET W/RUBBER HOSE JOINT (YARD SUPPLY)	-	1	1
7	HI-MACS TOP W/WASH BASIN	TOPCOUNTER(12t) &WHITE VITREOUS CHINA SINGLE LEVER MIXED FAUCET W/POP UP WASTE	-	1	1
8	UNDER CABINET	FLOATING TYPE UNDER CABINET 600(W)*750(H)425(D)_HOSPITAL ONLY, 600(W)*750(H)*525(D)	KME STANDARD	1	1
9	SHOWER MIXER	MIXING VALVE SINGLE LEVER TYPE W/TELEPHONE TYPE SHOWER HEAD & HOSE & SLIDE BAR	-	-	1
10	SHOWER MIXER	BUILT-IN SHOWER TYPE	-	1	-



No	Description	Specification	Model no	Q'TY / SET	
NO	Description	Specification	Model no	Shower	Bath
11	LED MIRROR	600W x 800H W/LED LIGHT	KME STANDARD	1	1
12	LED DOWN LIGHT	CEILING MOUNTING TYPE (AC 220V, 60Hz, 1Ø, 13W, IP44)	-	1	1
13	FLOOR SCUPPER & DRAIN / WASTE PIPE	SUS 304 FRAME W/Ø150 SUS 304 GRATING & 40A SPP W/RUBBER HOSE JOINT	KME STANDARD	1	1
14	EXHAUST VALVE	WALL MOUNTING TYPE W/ELBOW CONNECTOR KU-100/WHITE	KME STANDARD	1	1
15	DOOR SWITCH	POLAR WHITE (AC 250V 16AX / 1WAY, IP 20)	KME STANDARD KSW-F11	1	1
16	JUNCTION BOX (FOR LIGHT & RECEPTACLE)	ABS RESIN (6-GLAND, 9P), IP44	KME STANDARD	1	1
17	JUNCTION BOX (FOR 2W SPEAKER)	ABS RESIN (4-GLAND, 6P), IP44	KME STANDARD	1	1
18	SPEAKER(2W) (FOR U/T)	FLSH TYPE (YARD SUPPLY)	-	1	1
19	SHOWER BOOTH	HINGE TYPE : SUPPORT W/8T TOUGHEN GLASS (TRANSLUCENT)	KME STANDARD	1	-
20	TOWEL SHELF & BAR	SUS304 / 535 x 211 x 117	-	-	1
21	TOWEL HANGER	SUS &CHROME PLATED BRASS	-	1	-



No	Description	Specification	Model no	Q'TY	/ SET
NO	Description	Specification	Plodel no	Shower	Bath
22	SOAP DISH	PLASTIC & CHROME PLATED	-	1	1
23	SHOWER SHELF	GLASS & CHROME PLATED BRASS	_	1	1
24	DOUBLE PAPER HOLDER	SUS & CHROME PLATED BRASS	-	1	-
25	PAPER HOLDER (COLOR : BLACK)	SUS & CHROME PLATED BRASS	-	-	1
26	GRAB RAIL	SUS & CHROME PLATED BRASS	-	-	2
27	DOOR ADJUSTER	SUS & CHROME PLATED BRASS	-	1	1
28	СОАТ НООК	STAINLESS STEEL COLOR : SILVER	-	1	1
29	RECEPTACLE (FOR HAIR DRYER)	AC 250V, 50/60Hz, 16A	KME STANDARD	1	1
30	RECEPTACLE (FOR BIDET)	AC 250V, 50/60Hz, 16A	KME STANDARD	1	1
31	HOT WATER PIPE	Ø12 PVC COVERED COPPER PIPE W/BITE TYPE UNION BALL VALVE (Ø12xPF1/2") W/ SUS FLEX. HOSE (L=300, PT1/2" MALE)	KME STANDARD	1	1
32	FRESH WATER PIPE	Ø12 PVC COVERED COPPER PIPE W/BITE TYPE UNION BALL VALVE (Ø12xPF1/2") W/ SUS FLEX. HOSE (L=300, PT1/2" MALE)	KME STANDARD	1	1



No	Description	Specification	Model no	Q'TY / SET	
NO	Description	Specification	Model no	Shower	Bath
33	BATH TUB	GLASS FIBER REINFORCED PLASTIC(SMC) W/OVER FLOW WHITE (720X × 1500L)	KME STANDARD	-	1
34	GLASS PARTITION	AL, FRAME W/8.0T TOUGHEN GLASS(TRANSLUCENT)	KME STANDARD	-	1
35	STOP V/V (FOR BIDET)	CHROME PLATED BRASS	-	1	1
36	WASTE BASKET	ABS(WHITE), 6LITER 225(W) x 240(H) x 135(D)	-	1	1



Bath & Shower Type

GENERAL UNIT

KME UNIT TOILET provides type-specific functions, is durable, designed and systemized, and provides one finished product.

We can directly produce and supply products of Various designs, such as shower booth type, bathtub type as well as the standard of the customer.








GENERAL TYPE **PREFABRICATED WET UNIT**


We can directly produce and supply products of various designs,

such as shower booth type, bathtub type, as well as the standard of the customer.



SHOWER TYPE

- \cdot Direct production and supply of products.
- \cdot Create as requested by the customer.



BATH TYPE

- \cdot Direct production and supply of products.
- \cdot Create as requested by the customer.



No	Description	Specification	Model no	Q'TY / SET		
NO	Description	Specification	Piodel no	Shower	Bath	
1	FLOOR	NON-SLIP MOSAIC TILE & ON 3.2mm STEEL PLATE	-	1	1	
2	INSIDE WALL PANEL	PVC LAMINATED ON 0.6mm GALV'D STELL PLATE W/15mm MINERAL WOOL, TOTAL THK. 30mm	-	1	1	
3	OUTSIDE WALL PANEL	PVC LAMINATED ON 0.6mm GALV'D STEEL PLATE W/15mm MINERAL WOOL, TOTAL THK. 20mm	-	1	1	
4	DOOR & FRAME	BLADE : PVC FILM LAMINATED ON 0.6mm GALV'D STEEL SHEET CLEAR SIZE : 600(W) x 1800(H), 800(W) x 1800(H)_111 RM. ONLY FRAME : BAKED ENAMEL PAINTED ON 1.6mm STEEL PLATE	-	1	-	
		BLADE : PVC FILM LAMINATED ON 0.6mm GALV'D STEEL SHEET CLEAR SIZE : 600(W) × 1800(H) FRAME : BAKED ENAMEL PAINTED ON 1.2mm STEEL PLATE	-	-	1	
5	BATH TUB	GLASS FIBER REINFORCED PLASTIC(SMC) W/OVER FLOW WHITE	-	-	1	
6	WATER CLOSET	WALL MOUNTED WHITE VITREOUS CHINA VACUUM TYPE (VACDRIN)	-	1	1	
7	SOIL PIPE (VACUUM SYSTEM)	Ø50 OUTLET W/RUBBER HOSE JOINT	-	1	-	
	WASH BASIN	WHITE VITREOUS CHINA SINGLE LEVER FAUCET W/POP UP WASTE	-	-	1	
8	WASH BASIN (CORNER TYPE)	WHITE VITREOUS CHINA SINGLE LEVER FAUCET W/POP UP WASTE	-	1	0	



No	Description	Specification	Model no	Q'TY	/ SET
NO	Description	Specification	Model no	Shower	Bath
9	SHOWER MIXER	THERMOSTATIC MIXING VALVE W/TELEPHONE TYPE SHOWER HEAD & HOSE & SLIDE BAR	-	1	-
10	BATH MIXER	THERMOSTATIC MIXING VALVE W/TELEPHONE TYPE SHOWER HEAD & HOSE	-	-	1
11	TOILET CABINET	MOULDED PLASTIC BODY W/MIRROR (TC01-AC2-C1)	-	-	1
11	TOILET CABINET (CORNER TYPE)	MOULDED PLASTIC BODY W/MIRROR (TC04-SC2-C1)	-	1	-
12	FLOOR SCUPPER & DRAIN / WASTE PIPE	SUS 304 FRAME W/Ø150 SUS 304 GRATING & 40A SPP W/RUBBER HOSE JOINT	-	2	1
13	SHOWER CURTAIN	WATER PROOF TYPE CURTAIN WITH AL. RAIL	-	-	1
15	SHOWER CORTAIN	POLYESTER CURTAIN WITH AL. RAIL	-	1	-
14	TASSEL HOOK	CHROME PLATED BRASS(CTH-01)	-	1	1
15	HOT WATER PIPE	Ø12 PVC COVERED COPPER PIPE W/BITE TYPE UNION BALL VALVE (Ø12xPF1/2") W/ SUS FLEXIBLE HOSE(300L)	-	1	1
16	FRESH WATER PIPE	Ø12 PVC COVERED COPPER PIPE W/BITE TYPE UNION BALL VALVE (Ø12xPF1/2") W/ SUS FLEXIBLE HOSE(300L)	-	1	1
17	EXHAUST VALVE	KU-100/WHITE WALL MOUNTING TYPE W/ELBOW CONNECTOR	-	1	1



No	Description	Specification	Model no	Q'TY	/ SET
NO	Description	Specification	Model no	Shower	Bath
18	JUNCTION BOX (FOR LIGHT)	ABS RESIN (4-GLAND, 6P), IP44	-	1	1
19	JUNCTION BOX (FOR SPEAKER)	ABS RESIN (4-GLAND, 6P), IP44	_	1	1
20		LED11W, CEILING MOUNTING TYPE W/SHAVER SOCKET, IP44 (AC 220V, 60Hz, 1Ø), RECEPTACLE(UNIVERSAL TYPE) WITH ISOLATION TRANSFORMER	-	-	1
20	MIRROR LIGHT	LED 8W, CEILING MOUNTING TYPE W/SHAVER SOCKET, IP44 (AC 220V, 60Hz, 1Ø) WITH ISOLATION TRANSFORMER	-	1	-
21	DOOR SWITCH	KSW-F11, POLAR WHITE (AC 250V 16AX / 1WAY, IP 20)	-	1	1
22	SPEAKER(1W) (FOR U/T)	W/T FLUSH TYPE 1W SPEAKER (YARD SUPPLY)	-	1	1
23	SHOWER COAMING	2.0t SUS PLATE W/Ø12.7 SUS ROUND BAR (HEIGHT : 100mm)	-	1	-
24	CORNER SHELF	SUS & CHROME PLATED BRASS(KS-02)	-	1	-
25	TOWEL BAR	SUS & CHROME PLATED BRASS(TB-03)	_	1	1
26	SOAP DISH FOR WASH BASIN	STAINLESS STEEL(SD-04)	-	1	1
27	SOAP DISH FOR SHOWER	SUS & CHROME PLATED BRASS(SD-03)	-	-	1



No	Description	Specification	Model no	Q'TY / SET	
NO	Description	Specification	Model no	Shower	Bath
28	PAPER HOLDER	SUS & CHROME PLATED BRASS(PH-03)	-	1	1
29	GRAB RAIL	SUS & CHROME PLATED BRASS(GR-03)	-	2	2
30	COAT & HAT HOOK	SUS & CHROME PLATED BRASS(CH-02)	-	1	2
31		SUS & CHROME PLATED BRASS(KDA-02)	-	-	1
51	DOOR ADJUSTER	SUS & CHROME PLATED BRASS(938.64.002)	-	1	-
32	TOILET BRUSH	SPONGE TYPE	-	-	1
52	TOILET BRUSH	BRASS CHROME PLATED & PLASTIC (TOILET BRUSH HOLDER-02)	-	1	-
33	CLOTHES LINE	STAINLESS STEEL(KL-01)	-	-	1



HIGH-END / GENERAL TYPE Technical specifications

Wall Panel

 \cdot Surface finish : 0.6mm thickness galvanized steel sheet finished with decorative material

· Standard width : 510mm, Maximum Length : 2400mm

Туре	Model no.	Thickness	Fire class	Weight	Sound reduction	Thermal transmittance
	W-30	30mm	В-0	12kg/m²	STC 29dB	1.62kcal/rďh°C
	W-30D	45mm	B-15	15kg/m²	STC 29dB	0.81kcal/m²h℃
	W-50	50mm	B-15	19.2kg/㎡	STC 39dB RW 42dB	0.52kcal/rďh℃
······································	W-80	Min. 80mm	B-15	24kg/m²	STC 44dB	0.48kcal/rdh℃



HIGH-END / GENERAL TYPE Technical specifications

Ceiling Panel

 \cdot Surface finish : 0.6mm thickness galvanized steel sheet finished with decorative material

 \cdot Standard width : 510mm, Maximum Length : 2400mm

Туре	Model no.	Thickness	Fire class	Weight	Sound reduction	Thermal transmittance
	C30	30mm	В-0	12kg/m²	STC 52dB	1.62kcal/m²h°C
	C30D	45mm	B-15	15kg/m²	STC 53dB	0.81kcal/m²h°C
Incl .Steel deck	C30A	30mm	В-0	12kg/m²	-	1.62kcal/㎡h℃



HIGH-END / GENERAL TYPE Technical specifications

Approval certificates

Turne	Fire elece	Classification / Authority				
Туре	Fire class	ABS	DNV	KR	LR	BV / MED
KME-UT-W30	В-0	0	0	0	0	0
KME-UT-C30	В-0	0	0	0	0	0
KME-UT-C30A	В-0	0	0	0	0	0
KME-UT-W50	B-15	0	0	0	0	0
KME-UT-W80	B-15	0	0	0	0	0
KME-UT-C30D	B-15	0	0	0	0	0



MARINE SHIP NAME BOARD LED LIGHTING

SHIP'S NAME BOARD

• KME'S SHIP NAME BOARD LED LIGHTING IS ABLE TO BE PRODUCED ACCORDING TO CUSTOMER'S REQUEST.

LED LAMPS IN THE SHIP NAME BOARD LED LIGHTING ARE VERY BRIGHT IN THE NIGHT TIME AND ENERGY EFFICIENT.

· IN ADDITION, OUR PRODUCTS CAN MEET IP 56

5

MARINE SHIP NAME BOARD LED LIGHTING

SHIP'S NAME BOARD

KEY FEATURE

- \cdot SIZE : STANDARD OR CUSTOM MADE
- · BODY MATERIAL : STAINLESS STEEL /WHITE EPOXY

POWDER COAT AND STOVE


ENAMELLED(MUNSELL NO. N-9.3)

- · FRONT PANEL : POLYCARBONATE 4mm
- · PANEL COLOR : WHITE, PANEL TEXT : BLACK

· IP GRADE : IP56







LABORATORY FURNITURES & EQUIPMENTS





LABORATORY FURNITURES & EQUIPMENTS






LABORATORY FURNITURES & EQUIPMENTS









				RAPHA O' LIOU
PRESSURE TRANSMITTER EXPLOSION PROOF TYPE	BEAD HEAD UNIT	TROLLEY FOR CYLINDER	FLOW METER / MUMIDIFIER	PORTABLE OXYGEN KIT
MASK & ACCESSORIES	MEDICAL BED	EXAMINATION COUCH	STRETCHER	BASKET STRETCHER











WORKSHOP EQUIPMENTS





WORKSHOP EQUIPMENTS






VISE



GYMNASIUM EQUIPMENTS





GYMNASIUM EQUIPMENTS






WALL BAR




ENTERTAINMENT EQUIPMENTS





ENTERTAINMENT EQUIPMENTS





IT RELIEVES FATIGUE

SAUNA BOOTH

We can supply customized products according to customer's request.


SPRUS is used for the sauna booth wood, and it is manufactured according to the site conditions so that it can be supplied to ships.

It is made of tempered glass so that you can see the inside of the sauna room, and a piano hinge is attached to the door to increase its durability.

There is no risk of burns as the parts that can come into contact with the human body are finished with wood.

For a comfortable environment, a temperature controller was installed, and an air ventilation system was installed.








IT RELIEVES FATIGUE

SAUNA BOOTH



- · **INSIDE / OUT SIDE** : WOOD(SPRUS)
- **SIZE** : Custom Production
- · SAUNA HEATER : 6.6kW / 8.0kW / 10kW
- **BENCH** : TWO TIRED
- · EMERGENCY PUSH BUTTON WITH THERMOSTAT
- · VENTILATION DUCT
- · TOUGHED GLASS HINGED DOOR
- · HEATER GUARD
- · NON COMBUSTIBLE PLATER FOR HEATER
- ─ · CONTROL PANEL



IT RELIEVES FATIGUE


SAUNA BOOTH

Take a shower and open the door. Close your eyes and listen to what's inside you.

Pour a ladle of water over a hot stone and listen for hiss. As the steam rises like a cloud, your mood will also feel liberated with good heat.

A grill designed to effectively circulate warm air and a nice design will keep you energized and refreshed.







Power source : AC440V, 3PH

Output : 6.6kW / 8.0kW / 10kW





GALLEY, LAUNDRY AND PANTRY EQUIPMENT FOR SHIPS



COMPANY

COCINAS BURAGLIA was founded in 1922 in the city of Valencia, Spain. It started supplying furniture and equipment for domestic use. Decades later, in the late 1950's the company changed its strategy and became specialized in the marine market which started growing rapidly together with the country's economy supplying marine accommodation equipment and furniture for galley, laundry and pantry.

Since 1990 the company has crossed borders and expanded its business through other European countries like France and the North Sea countries where the offshore business started to demand specialized products to meet the high standards required by their safety and quality rules.

<u>COCINAS BURAGLIA</u> has an ongoing commitment to quality and has held certification to ISO 9001 standards since 2006. So far, the company has supplied equipment for thousands of maritime vessels.







CONSERVATION Reach-In Chest freezers and **Reach-In freezers Cooled showcases Under counters Cold counters** refrigerators bottle coolers Refrigerators & absorption refrigerators **Beverage dispensers Ice cream Makers** Ice makers Water coolers



PREPARATION


















CLEANING LAUNDRY Image: Cleaning of the second s





HIGH QUALITY

DNV			Certification		
SURVEY REPORT REPORT No: N1427BGF		VERITAS	Awarded to COCINAS BURAGLIA SL		
		Certification			
Particulars of Product					
Product Name:	Deep Fat Fryer	σ	CL DE LA MARTINA, 2 POL IND MORET - 46210 - PICANYA -		
Type designation:	SOLAS	U	VALENCIA - ESPAÑA		
Application/context:	Deep Fat Fryer				
Serial/Tag no:	. <u>N.A.</u>		Bureau Veritas certification certifies that the Management System has been audited		
The product is intended for:	SOLAS		found to be in accordance with the requirements of standard:		
Requirements are based on:	SOLAS		STANDARD		
The product / maturial has been marked: N142780F on: CP Particulars of Vendor and Purchaser Vendor: <u>COCINAS BURACILA, S.L.</u> Particulars: <u>COCINAS BURACILA, S.L.</u> Parthaum: <u>COCINAS BURACILA, S.L.</u>		ISO 9001:2015			
Particulars of Vendor and Purch	aser	(U)	150 7001.2	2013	
Vendor:	COCINAS BURAGLIA, S.L.		and a second		
Vendor reference:	Renovación del certificado DNV project A0338765		Scope of certification:		
Purchaser:	COCINAS BURAGLIA, S.L.)e	DECIDN PROPURTION ACCEMPLY DISTRIBUTION		
Purchaser reference:			DESIGN, PRODUCTION, ASSEMBLY, DISTRIBUTION,		
Issued of Area NBCMC Berla on 2021-18-24			COMMERCIALIZATION AND AFTER SALES SERVICES OF GALLEY, LAUNDRY AND PANTRY EQUIPMENT FOR SHIPS.		
		D .			
		(D			
	This document has been divitally signed as	Bureau	SHIPS.		
	DNV 3 This document has been digitally signed an therefore not have handwritten signature		the second se		
	Lacave Azpeitia, Juan Javier	m			
	Surveyor		Construction (Construction)		
	²⁷ A _L , Cl ^A Surveyor				
	Surveyor Surveyor		Certificate Number:	E5121192- 1	
	¹² A ₁₄ of ¹ Surveyor		Certificate Number: Original approval date:	ES121192-1 18-08-2006	
	™A∟on™ Surveyor				
	MALON [®] Surveyor		Original appreval date:	18-08-2006	
	™A _N on [™] Surveyor		Original approval date: Certification/Renovation Audit:	18-08-2004 21-05-2021	
	Surveyor		Original approval date; Certification/Renovation Audit; Expiry date of previous cycle;	18-08-2006 21-05-2021 22-06-2021	
	Surveyor		Original approval date. Certification/Renvation Audit: Expiry data of previous cyclen Effective date. Certificate expiration date:	18-08-2006 21-05-2021 22-06-2021 23-06-2021 23-06-2021 22-06-2026	
	Surveyor Balan potenti el 1 fa toble d'ago possen y la Marca Sun avesara y la su tobleg d en patier estatet el 1 fa toble de la possen y la Marca Sun avesara y la su tobleg d		Original appreval date: Certification/Renovation Audit: Expiry date of previous cycle: Effective date:	18-08-2006 21-05-2021 22-06-2021 23-06-2021 23-06-2021 22-06-2026	

QUALITY

Our quality is guaranteed by our Quality Policy and the following certifications:

- · CE Mark
- · ISO 9001:2015

· SOLAS certified by DNV

For us, while it's very important to have certifications, surpassing the standards that our clients expect from us is paramount. These standards are high enough to deliver furniture and equipment that complies with all the regulations of markets such as USPH, NORSOK, GOST, PECAL and so on. If requested, we can certify our equipment as per any standard required.

In **COCINAS BURAGLIA** we believe that there cannot be quality without safety. All of our industrial equipment intended for maritime use is designed with the hygiene and safety as key factors.





CATERING FURNITURE



BURAGLIA GALLEYS MANUFACTURE TAILORED FURNITURE

We manufacture tailored stainless steel furniture. Furniture is manufactured in stainless steel AISI 304L 2B (AISI 316 on demand).

Main features:

 \cdot Reinforced counter tops either with plywood board or stainless steel omegas


- \cdot Back splash have 100 mm height
- \cdot Thickness of the stainless steel sheet is at least 1 mm
- · Height adjustable feet
- \cdot All shelves are provided with sea rolling bars
- \cdot Doors and drawers can include locks

The range of furniture comprises working tables, sink tables, coffee tables, cupboards, shelves, racks, key cabinet, lockers, plinths, gutters, extraction hoods, self-service furniture, and medicine cupboard and so on. We supply whatever you might need in a galley, a laundry, a messroom, a locker room and a hospital.





CATERING FURNITURE





MARAHRENS **SAFETY SIGNS**







IMO safety signs

Our extensive sign portfolio complies with IMO regulations and ISO standards.



Means of escape signs (MES) These safety signs indicate the escape route within a ship and provide directional guidance from any area within the ship to a safe place assembly station



Emergency equipment signs (EES) They indicate the exact location of first aid facilities, first aid equipment, or portable safety equipment, the type of facility or equipment and any instructions for its use.



Life saving systems and appliances signs (LSS) Safety signs of this type indicate the exact location or storage of the life-saving equipment, the type of equipment, the quantity and any instructions for its correct



Fire-fighting equipment signs (FES) These safety signs indicate the exact location of the fire-fighting equipment, the type of equipment and any instructions for its effective and safe use.



Prohibiton signs (PSS) This signage draws attention to restrictions and prohibitions on various actions by people. Also in accordance with the ISPS Code (International ship and port facility security code)



Mandatory action signs (MSS) Safety signs of this type used to instruct persons of a specific course of action that shall be followed. They indicate commandments on board.



Warning signs (WSS) These signs used to warn persons of possible dangerous conditions, hazards and risks that exist on board a ship. They mark obstacles and danger points.





(\$1\$) This safety signage is used to draw attention tospecialised safety and fire protection equipment on board the ship. The symbols are in accordance with the Fire Control Plan.



substances. Clear and standard-compliant labeling of hazardous substances is extremely important both on land and at sea


Safety on cruise ships, passenger ferries, yachts and offshore platforms is an absolute priority. In an emergency, signage, markings and instructions must be quickly and clearly recognizable for quests, passengers and crew. Marahrens stands for reliable signage on board and meets the requirements of the classification societies, SOLAS, IMO as well as other maritime standards.


All signs are produced from high-quality base materials that can withstand the harsh weather conditions at sea on the outside deck or inside. The signage is available in (photoluminescent) vinyl as well as rigid PVC The base material complies with DIN 67510. All signage is self-adhesive for easy installation and can be purchased in different sizes



MARAHRENS EXIT LED SIGNS









MARAHRENS EXIT LED SIGNS







Recess mounting Homogeneous illumination in an elegant, flat construction

The sign can be inserted or removed from the preassembled body with an integrated click **mechanism 1**. This system makes it possible to install the base body at an early stage. The subsequent sign insertion prevents possible damage during the construction phase.







Quick assembly on site

The base body (including the cover) is quickly and easily mounted on site in the existing ceiling cut-out with 4 fixing screws 2 (not included in the delivery).

Materials

The slim design of the lid is available in the following material versions. Anodised aluminum with a brushed stainless steel look, aluminum powder coated according to RAL color scale as stainless steel in V4A brushed as well as V2A chromed. Further pictograms are also available.

KME Co., Ltd.



The sign can be inserted or removed from the preassembled body with an integrated click mechanism **1**. This system makes it possible to install the base body at an early stage. The subsequent sign insertion prevents possible damage during the construction phase.





Quick assembly

The base body (including the cover) **1** is quickly and easily mounted on the ceiling or wall with 4 fixing screws (not included in the delivery). Sign can be easily clicked into mounted base.

Materials

The lid is available in the following material versions. Anodised aluminum with a brushed stainless steel look, aluminum powder coated according to RAL color scale as stainless steel in V4A brushed as well as V2A chromed. Further pictograms are also available.





MARAHRENS PIPE MARKING TAPES





Mark the content and flow direction of the pipes on board according to ISO 14726 with our products

(new ISO standard 20560)



- · Application on board
- Pipe markings are used on board as follows:
- Every pipe with a **substance** must be marked **in every room**
- A pipe marking must be installed at every point that the pipe
- passes through a wall, a ceiling or a floor
- Even **valves** or **pumps** must be marked
- In case of lengthy pipes, a marking will usually be installed in **certain distances (approx. 3-5 meters)**

Group	Pipe contents	Sign color	Font color	Add. color
1	Water	green	🔲 white	
2	Steam	red	🔲 white	
3	Air / vacuum	grey	black	
4	Flammable gases	yellow	black	red
5	Non-flammable gases	yellow	black	black
6	Acid	orange	Black	
7	Alkalis	purple	🔲 white	
8	Flammable liquids & solids	brown	🔲 white	red
9	Non-flammable liquids & solids	brown	🖂 white	black
0	Oxygen	blue	u white	




HAPPICH LLL(LOW LOCATION LIGHTING) SYSTEM

LOW LOCATION LIGHTING – the well know term for "ESCAPE ROUTE MARKING" components mounted near the floor to guide passengers and crew to the right and safe areas in case of emergency.





HAPPICH LLL(LOW LOCATION LIGHTING) SYSTEM



Application

- · Shipbuilding
- Buildings
- \cdot Offshore platforms

Norm

· ISO 15370:2010

Single components

- \cdot base profile
- décor profile
- LED-strip
- protection cover
- \cdot power supply box
- LED-signs
- exit
- stair
- \cdot arrow

Function

• Marking along escape routes for emergency evacuation; can also be used as a design element (ambient lighting)


Versions

- · 2 wire system: LED-strip, 2 wire, 200mm LED-distance with décor profile
- · 3 wire system: LED-strip, 3 wire, 200mm LED-distance with décor profile



KME Co., Ltd. STRIP LIGHT (EDGE LIGHT)





Application

- · Shipbuilding
- Buildings
- · Offshore platforms

SPECIFICATION


- · COLOR TEMPERATURE : 4000K
- · INPUT POWER SOURCE : AC 220V
- · OUTPUT : DC 24V
- · OUTPUT CURRENT : 3.8A
- · CAPACITY : 30W
- · COLOR : WHITE
- · SIZE : 75 X 35 X 2400 mm





VIDEO CONFERENCE SOLUTION

KME's video conference solution is enable quick adoption with meeting capabilities on board that make it easy to start, join, file's transfer, share of screen, meeting result, ideas.



· Collaborators :

Provide Collaborators with all-in one meeting room collaboration devices so crew are able to use seamlessly meeting.

Concentrators :

Equip the occasional meeting joiner with cost-effective devises so crew are able to stay connected during the conference meeting






HIGH-EFFICIENCY VIDEO CONFERENCE

VIDEO CONFERENCE SOLUTION


BEAM PROJECTOR & 75" UHD TV CONFERENCE ROOM

- · BEAM PROJECTOR
- SCREEN
- · 75" UHD TV

- · VIDEO CAMERA
- · CONFERENCE MIC/PSEAKER
- · PERSONAL PC
 · AMPLIFIER









EASY-TO-ACCESS

SCREEN GOLF

FEATURE

- · Analysis swing
- · Providing rounding game for real game
- \cdot Unmanned operation
- · Repetition training
- \cdot Offline mode

PROGRAM

· DRIVING RANGE, STROKE, LONGEST GAME, FIELD, NEARPIN, SHOT 18HOLE, PUTTING, PUTTING ROUNDING

CONSIST

· BEAM PROJECTOR, SCREEN AUTO TEE-UP, SWING PLATE, GOLF CLUB, IRON STAND, BALL, etc

SIZE

· 9000 x 4635 (mm)

CC

• 90 CC





EASY-TO-ACCESS

SCREEN GOLF




SCREEN (FABRIC) Auto Tee up (RETARDANT (185mm / 160mm GENERAL / LOW-/ 127mm)

NOISE)

SWING PLATE (AUTO TEE-UP BUILT IN)


V-VIP Round Screen





EASY-TO-ACCESS

SCREEN GOLF



ROOM SIZE

· 4100 x 9000 x 5100 (CEILING 3200mm)

SCOPE OF SUPPLY

- · SCREEN GOLF SYSTEM PACKAGE
- · AUTO TEE UP
- SCREEN
- · BOOTH(WALL/FLOOR/CEILING)
- · ENGINEERING
- · INSTALLATION



GLOBAL SERVICE NETWORK






CERTIFICATION



- 1. ISO9001:2015
- 2. ISO14001:2015
- 3. Laboratory
- 4. KR Cert. (Anti icing CP)
- Cert. of patent (Ground material)
- Cert. of patent
 (Ship Name Board)
- Cert. of patent
 (LED Navi & Signal light)
- Cert. of patent
 (Navi & Signal light)
- 9. RMRS CERT. (EX JB)
- 10 IECEx Cert. (EX JB)







ISO 9001 : 2015



HSE (HEALTH, SAFETY AND ENVIRONMENT)







THANK YOU

www.h-kme.com



• ADDRESS : 29, Nakdong-daero 1302, beon-gil, Sasang-gu, Busan, 46910
 • TEL : +82-51-327-2670 • FAX : +82-51-327-2673 • E-mail : sales@h-kme.com